

**What is claimed is:**

1. Method for cooling a gas turbine system comprising a compressor that takes in suction air on the inlet side and compresses it to compressor end air that is available on the outlet side, a combustor in which a fuel is burned by using the compressor end air while resulting in the formation of hot gas, as well as a turbine in which the hot gas is expanded while providing work output, in which process compressed air is removed from the compressor, is fed as cooling air for cooling inside an internal cooling channel through thermally loaded components of the combustor and/or the turbine, is then compressed and added to the compressor end air, wherein, in the manner of a targeted leakage, a small part of the cooling air is fed for film cooling into the turbine stream through drilled film cooling openings provided on the components.

2. Method as claimed in Claim 1, wherein the thermally loaded components include the walls of the combustor and/or walls of the transition pieces and/or housing parts of the turbine and/or rotor parts of the turbine and/or blades of the turbine.

3. Method as claimed in Claim 2, wherein the blades of the turbine are cooled with the cooling air, and that the drilled film cooling openings are located on the leading blade edges and/or the trailing blade edges.

09073373.060501  
T05090-E/E/2860

4. Method as claimed in Claim 2, wherein the turbine includes a plurality of rows of blades, and that the cooling air successively flows through the rows of blades.

5. Method as claimed in Claim 1, wherein the compressor of the gas turbine system itself is used for compressing the cooling air after the cooling process.

6. Method as claimed in Claim 1, wherein an external compressor is used to compress the cooling air after the cooling process.

7. Method as claimed in Claim 6, wherein the cooling air is compressed by the external compressor to the pressure of the compressor end air, and that the compressed cooling air is added directly to the compressor end air.

8. Method as claimed in Claim 1, wherein the cooling air is cooled after the cooling process and prior to compression.

9. Method as claimed in Claim 1, wherein the cooling air is cooled after removal from the compressor to a lower temperature before it is used for the cooling of thermally loaded components.

09072373-060504

10. Method as claimed in Claim 8, wherein a cooler is used to cool the cooling air.

11. Method as claimed in Claim 8, wherein water is injected directly into the cooling air in order to cool the cooling air.

12. Method as claimed in Claim 8, wherein the cooling air is cooled with the compressor end air by using a heat exchanger.

13. Method as claimed in Claim 12, wherein the cooling air, after passing through the heat exchanger, is further cooled using yet another cooling medium.

14. Apparatus for cooling a gas turbine system comprising: a compressor that takes in suction air on the inlet side and compresses it to compressor end air that is available on the outlet side, a combustor in which a fuel is burned by using the compressor end air while resulting in the formation of hot gas, as well as a turbine in which the hot gas is expanded while providing work output, whereby, in order to cool thermally loaded components of the combustor and/or the turbine, first cooling lines from the compressor and/or the outlet of the compressor to components and second cooling lines from the components back to the compressor and/or the outlet of the compressor are provided, and wherein the components to

1065990 "E3E7800

be cooled are provided with drilled film cooling openings that communicate with the first and second cooling lines.

15. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein the cooled components include blades of the turbine, and that the drilled film cooling openings are located on the leading blade edges and/or the trailing blade edges.

16. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein the second cooling lines merge into the compressor at an intermediate pressure level.

17. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein an external compressor is located in the second cooling lines, and that the second cooling lines merge into the outlet of the compressor of the gas turbine system.

18. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein a cooler is located in the second cooling lines.

19. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein an injection device for injecting water into the cooling air is located in the second cooling lines.

20. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein a heat exchanger through which the compressor end air flows is located in the second cooling lines.

21. Apparatus for cooling a gas turbine system as claimed in Claim 20, wherein a cooler operated with a different cooling medium is located downstream from the heat exchanger.

22. Apparatus for cooling a gas turbine system as claimed in Claim 14, wherein means for cooling the cooling air, in particular in the form of a cooler are located in the first cooling lines.